OF COURSE
A STATE OF S
Continue of the B

	<u>Tech</u>	nical Specifications of Tractor.	Offered
		S. S	Specifications
	Particulars	Requirements	
	General .	Right hand driven with Two Wheel Drive(2WD), suitable for normal and rough road driving in Nepal at an altitude up to 2000 meter and in ambient temperature -5 to 50 degree centigrade. Having kerb weight minimum 1900 kg.	Make: Model:
			Mfg. Year:
	,	Type: 4-Stroke, Direct Injection, Water-cooled Diesel Engine HP Category: Min, 47 HP or above.	Make:
	Engine	Engine Capacity: Not less than 3067±2%CC Engine Rated RPM: 2200	Model:
		No of Cylinder: Not less than 3 Air Filter: Oil bath With Cleaner or Dry air cleaner. Cooling System: Water Cooled	
)	Emission Standard	The Emission Standard of the vehicle should be of Nepal Vehicle Mass Emission Standard-2069, Which is to be certified by Department of Transport Management, Nepal	
;	Transmission	Type: Heavy Duty Sliding/Constant Mesh/Synchromesh Gear-box: 8- Forward and 2- reverse	
5_	Steering	Mechanical/Power Steering.	
7	Gauges	To include speedometer, fuel etc. as necessary for efficient operation and maintenance	

20-00 02 2 Eq. Miraj Kumar Sah

Er. Miraj Kumar Sah


Er. Miraj Kumar Sah



8	Ground Clearance	High Ground clearance preferred, minimum 440mm (Real Wheel).	r
9	Power Take Off	PTO RPM: 540@governed RPM	*;
10	Clutch	Dual Clutch	
11	Tires	Standard Size, factory fitted tubeless.	
12	Starting	Self-starter	
13	Brakes	Multi plate Oil immersed brakes	
14	Wheel	2 WD, Rim/Cast Wheel,	
15	Hydraulic and implement linkage	3 point linkage, Hydraulic system with automatic depth, position control, draft control and mixed controlled	
16	Hydraulic lift pump	Gear type pump with delivery of at least 20 litres per minute at	
		rated engine speed	
	Electrical	Battery 12v,100Ah, Alternator (12v,40A) and starter motor	
	instruments	(12v,5kw)	
18	Essential accessories	a. High sensitive hydraulic system b. Big rear tyres c. Multi speed and reverse speed PTO d. Adjustable sliding seats e. Telescopic stabilizer bar f. Neutral Safety Switch g. Tap off connections for Tripping Trailer h. Top link, canopy, hook i. Seven point electric connection	

goro 102/24 Er Nirai Krimar Sah

2012/2/23



		\$ ·	
	Lifting capacity	Lower line top with minimum 2000kg	
	Instructions	All signs and instructions in the vehicle shall be in English.	
	Manuals	Copy of the Operator's and Owner's instructions in English shall be supplied with each vehicle	
2		A set of tools as required for general maintenance shall be	
	Tools	supplied with in a lockable tool box for each unit.	
3	Color	Standard color	
1	Proven performance	The Tractor offered shall be under standard production by the manufacturer and should be current model.	
5	Warranty	Manufacturer shall provide a minimum one year of warranty after acceptance.	
	Delivery	The unit 1 Tractor shall be delivered to: Baragadhi Rural Municipality Khopwa, Bara	

2000/02/259

Er. Nitaj Kumar Sali

1950012